

PATENT ABSTRACTS OF JAPAN

(11) Publication number: 04154731 A

(43) Date of publication of application: 27.05.92

(51) Int. CI

C07B 51/00

C07C227/20

C07C229/02

C07D209/20

C07K 1/06

C07K 5/10

// C07B 31/00

C07B 61/00

(21) Application number: 02277809

(22) Date of filing: 18.10.90

(71) Applicant:

SNOW BRAND MILK PROD CO

LTD

(72) Inventor:

KAWASAKI ISAHIRO KONISHI HIROAKI KAWANARI MASAMI

(54) DEPROTECTION METHOD

(57) Abstract:

PURPOSE: To carry out the deprotection of a protected functional group by the catalytic hydrogenation with H₂ released from a hydrogen-occluding alloy composed mainly of a compound having a CaCu5-type hexagonal crystal structure and containing Ni and a rare-earth element or Ca element as essential elements.

CONSTITUTION: A protected functional group is deprotected by the catalytic hydrogenation at 0-80°C with H₂ released from a hydrogen-occluding alloy composed mainly of a compound having a CaCu5-type hexagonal crystalline structure and containing R (rare-earth

element or Ca element) and Ni as essential elements. Preferably, the decomposition temperature of the alloy corresponding to the decomposition equilibrium pressure of 1 atm is ≤200°C and the average particle diameter of the alloy is $0.5\text{-}100\mu m$. Since the alloy has high catalytic activity in itself, the deprotection can be carried out in high efficiency under a high-safety condition (i.e., an H₂ gas pressure of <10kg/cm²) without using a catalyst. A large amount of H2 gas can be occluded in the alloy and the alloy is available at a low cost compared with conventional Pd or Pt catalyst and is durable to repeated use.

COPYRIGHT: (C)1992,JPO&Japio